

洗脱烘全自动洗衣机系列

Wash and dehydrate and dry the full-automatic washing machine series

XTH系列变频洗脱烘全自动洗衣机是我公司研制开发的新一代洗涤机械产品，独特的方式实现完全防震结构，有效的解决洗衣机脱水震动大这一致命的弱点。实现了洗脱烘一体化，是理想的洗涤机械产品。

Wash and dehydrate and dry the full-automatic washing machine in XTH series frequency conversion is the new generation who Our company develops the development washes the engineering products, the unique way realizes prevents the vibration structure completely, the effective solution washer dehydration vibrates the big this fatal weakness. Realized the elution to dry the integration, was the ideal wash engineering products.



型号Type	SXTH-120G	SXTH-160G	SXTH-220G
洗涤容量(kg) Washing capacity	12	16	22
烘干容量(kg) Drying capacity	12	16	22
噪音dB(A) Noise	70	70	70
工作电压(V) Washing voltage	AC110/220/380/415/440/50-60Hz		
洗涤转速(rpm) Washing speed	45	45	45
烘干转速(rpm) Drying speed	36	36	36
均布转速(rpm) Distribution speed	60	60	60
高脱转速(rpm) High Extract speed	600	600	600
洗涤电机功率(kw) Motor power	1.1	1.5	2.2
烘干电机功率(kw) Drying Motor power	0.2	0.2	0.2
烘干风机功率(kw) Power of Air Blower	0.55	0.55	0.55
洗涤加热器功率(Kw) Power of Heater	220V8/380V12		
烘干加热形式 Heating form	电、蒸汽、液化气、瓦斯、天然气		
烘干电加热器功率(Kw) Drying Power of Heater	220V8/380V12	220V10/380V14	220V10/380V18
每车耗水量(L) Water Consumption	200	240	300
每车洗涤耗汽量(Kg) Steam Consumption	≤18	≤18	≤25
每车烘干耗汽量(Kg) Drying Steam Consumption	20-30	25-35	36-45
装机容量(kw) Installed Capacity	220V18.7/380V29	220V21/380V29	220V22/380V34
蒸汽压力(MPa) Steam pressure	0.4-0.6	0.4-0.6	0.4-0.6
冷水进口尺寸(mm) Cold Water Inlet	φ20	φ20	φ20
蒸汽进口尺寸(mm) Steam Inlet	φ15	φ15	φ15
排水口尺寸(mm) Water Drain	φ50	φ50	φ50
整机重量(kg) Net weight	400	437	550
机器宽度(mm) width (L)	862	862	862
机器深度(mm) depth (W)	1045	1140	1275
机器高度(mm) height (H)	2028	2028	2028
1机门中心高度(mm) height center Door (h1)	634	634	634
2机门中心高度(mm) height center Door (h2)	1600	1600	1600



型号Type	XTH-15	XTH-20	XTH-25
洗衣容量 Laundry Capacity (kg)	15	20	25
滚筒转速 Drum speed (r/min)	780	780	780
额定电压 Rated voltage (V)	220	220/380	220/380
电机功率 Motor power (kw)	1.5	2.2	3
烘干功率 Drying power (kw)	9	9	12
烘干容量 Drying capacity (kg)	8	10	13
管道进口 Pipeline imports	DN20	DN20	DN25
排水口 Drainage outlet	DN40	DN40	DN50
滚筒尺寸 Roller size (mm)	Φ670 × 450	Φ750 × 450	Φ800 × 530
外形尺寸 Overall dimension (mm)	1100 × 970 × 1420	1100 × 1000 × 1420	1300 × 1350 × 1700
整机重量 Machine weight (kg)	600	700	750